

ALTO




Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Aluminum reflector - PMMA
 COB LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



IP20



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
ALT.2022.25	25W	3250Lm	95+	80+	3000-4000-6500K	700gr	Ø:210mm	Ø:227 D: 85mm
ALT.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	530gr	Ø:175mm	Ø:192 D: 85mm
ALT.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	470gr	Ø:160mm	Ø:175 D: 85mm
ALT.2022.12	12W	1560Lm	95+	80+	3000-4000-6500K	360gr	Ø:130mm	Ø:147 D: 75mm
ALT.2022.9	9W	1170Lm	95+	80+	3000-4000-6500K	300gr	Ø:105mm	Ø:117 D: 70mm
ALT.2022.6	6W	780Lm	95+	80+	3000-4000-6500K	280gr	Ø:85mm	Ø:97 D: 70mm