


AURA



Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Opal PMMA
 Power LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



| Product Code | Watt | Lumen | Power Factor | CRI | Light Color | Kg | Cut Size mm | Dimensions mm |
|--------------|------|--------|--------------|-----|-----------------|-------|-------------|---------------|
| ARA.2022.25 | 25W | 3000Lm | 95+ | 80+ | 3000-4000-6500K | 700gr | Ø:210mm | Ø:227 H:85 mm |
| ARA.2022.20 | 20W | 2500Lm | 95+ | 80+ | 3000-4000-6500K | 530gr | Ø:175mm | Ø:192 H:85 mm |
| ARA.2022.16 | 16W | 2000Lm | 95+ | 80+ | 3000-4000-6500K | 470gr | Ø:160mm | Ø:175 H:85 mm |
| ARA.2022.8 | 8W | 1000Lm | 95+ | 80+ | 3000-4000-6500K | 360gr | Ø:130mm | Ø:147 H:80 mm |
| ARA.2022.6 | 6W | 750Lm | 95+ | 80+ | 3000-4000-6500K | 300gr | Ø:105mm | Ø:117 H:70 mm |
| ARA.2022.6 | 6W | 750Lm | 95+ | 80+ | 3000-4000-6500K | 280gr | Ø:85mm | Ø:97 H:70 mm |