


DELTA WALL UP&DOWN



Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating

Extruded Aluminum
 Opal PMMA-Micro Prismatic
 Power LED
 120Lm/W
 220-240V AC 50/60 Hz
 Wall
 W:35mm H:100mm
 3000K-4000K-6500K
 >80
 DALI / 1-10V
 IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
DLT50/35.22	Wall Up & Down	22W	2640Lm	>80	3000-4000-6500K	35x100x500mm
DLT50/35.16	Wall Up & Down	32W	3840Lm	>80	3000-4000-6500K	35x100x500mm
DLT100/35.44	Wall Up & Down	44W	5280Lm	>80	3000-4000-6500K	35x100x1000mm
DLT100/35.64	Wall Up & Down	64W	7680Lm	>80	3000-4000-6500K	35x100x1000mm
DLT120/35.54	Wall Up & Down	54W	6480Lm	>80	3000-4000-6500K	35x100x1200mm
DLT120/35.78	Wall Up & Down	78W	9360Lm	>80	3000-4000-6500K	35x100x1200mm
DLT150/35.66	Wall Up & Down	66W	7920Lm	>80	3000-4000-6500K	35x100x1500mm
DLT150/35.96	Wall Up & Down	96W	11520Lm	>80	3000-4000-6500K	35x100x1500mm
DLT200/35.84	Wall Up & Down	88W	10560Lm	>80	3000-4000-6500K	35x100x2000mm
DLT200/35.128	Wall Up & Down	128W	15360Lm	>80	3000-4000-6500K	35x100x2000mm
DLT250/35.110	Wall Up & Down	110W	13200Lm	>80	3000-4000-6500K	35x100x2500mm
DLT250/35.160	Wall Up & Down	160W	19200Lm	>80	3000-4000-6500K	35x100x2500mm
DLT300/35.132	Wall Up & Down	132W	15840Lm	>80	3000-4000-6500K	35x100x3000mm
DLT300/35.192	Wall Up & Down	192W	23040Lm	>80	3000-4000-6500K	35x100x3000mm