

## FORM SUSPENDED




<b>Body</b>	Stainless Steel
<b>Diffuser</b>	Opal PMMA-Micro Prismatic
<b>Source of Light</b>	Power LED
<b>Lumen/Watt</b>	120Lm/W
<b>Input Voltage</b>	220-240V AC 50/60 Hz
<b>Mounting</b>	Suspended
<b>Dimensions</b>	H:70mm
<b>Light Color</b>	3000K-4000K-6500K
<b>CRI</b>	>80
<b>Options</b>	DALI / 1-10V
<b>IP Rating</b>	IP40
<b>Led lifetime</b>	100.000+



LED



IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (W:H:)
FRM3030SU/70.12	Suspended	12W	1440Lm	>80	3000-4000-6500K	300x300x70mm
FRM3060SU/70.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	300x600x70mm
FRM6060SU/70.36	Suspended	36W	4320Lm	>80	3000-4000-6500K	600x600x70mm
FRM30120SU/70.36	Suspended	36W	4320Lm	>80	3000-4000-6500K	300x1200x70mm
FRM60120SU/70.70	Suspended	70W	8400Lm	>80	3000-4000-6500K	600x1200x70mm
FRM120120SU/70.140	Suspended	140W	16800Lm	>80	3000-4000-6500K	1200x1200x70mm