

LAKE SUSPENDED




Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating

Extruded Aluminum
 Opal PMMA-Micro Prismatic
 Power LED
 120Lm/W
 220-240V AC 50/60 Hz
 Suspended
 W:52mm H:65mm
 3000K-4000K-6500K
 >80
 DALI / 1-10V
 IP40



IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
LKE50/52.11	Suspended	11W	1320Lm	>80	3000-4000-6500K	52x65x500mm
LKE50/52.16	Suspended	16W	1920Lm	>80	3000-4000-6500K	52x65x500mm
LKE100/52.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	52x65x1000mm
LKE100/52.32	Suspended	32W	3840Lm	>80	3000-4000-6500K	52x65x1000mm
LKE120/52.27	Suspended	27W	3240Lm	>80	3000-4000-6500K	52x65x1200mm
LKE120/52.19	Suspended	39W	4680Lm	>80	3000-4000-6500K	52x65x1200mm
LKE150/52.33	Suspended	33W	3960Lm	>80	3000-4000-6500K	52x65x1500mm
LKE150/52.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	52x65x1500mm
LKE200/52.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	52x65x2000mm
LKE200/52.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	52x65x2000mm
LKE250/52.55	Suspended	55W	6600Lm	>80	3000-4000-6500K	52x65x2500mm
LKE250/52.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	52x65x2500mm
LKE300/52.66	Suspended	66W	7920Lm	>80	3000-4000-6500K	52x65x3000mm
LKE300/52.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	52x65x3000mm