




LAKE SURFACE



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Surface
Dimensions	W:52mm H:65mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
LKE50.S/52.11	Surface	11W	1320Lm	>80	3000-4000-6500K	52x65x500mm
LKE50.S/52.16	Surface	16W	1920Lm	>80	3000-4000-6500K	52x65x500mm
LKE100.S/52.22	Surface	22W	2640Lm	>80	3000-4000-6500K	52x65x1000mm
LKE100.S/52.32	Surface	32W	3840Lm	>80	3000-4000-6500K	52x65x1000mm
LKE120.S/52.27	Surface	27W	3240Lm	>80	3000-4000-6500K	52x65x1200mm
LKE120.S/52.19	Surface	39W	4680Lm	>80	3000-4000-6500K	52x65x1200mm
LKE150.S/52.33	Surface	33W	3960Lm	>80	3000-4000-6500K	52x65x1500mm
LKE150.S/52.48	Surface	48W	5760Lm	>80	3000-4000-6500K	52x65x1500mm
LKE200.S/52.44	Surface	44W	5280Lm	>80	3000-4000-6500K	52x65x2000mm
LKE200.S/52.64	Surface	64W	7680Lm	>80	3000-4000-6500K	52x65x2000mm
LKE250.S/52.55	Surface	55W	6600Lm	>80	3000-4000-6500K	52x65x2500mm
LKE250.S/52.80	Surface	80W	9600Lm	>80	3000-4000-6500K	52x65x2500mm
LKE300.S/52.66	Surface	66W	7920Lm	>80	3000-4000-6500K	52x65x3000mm
LKE300.S/52.96	Surface	96W	11520Lm	>80	3000-4000-6500K	52x65x3000mm