



LAND SURFACE



Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating


Extruded Aluminum
Opal PMMA-Micro Prismatic
Power LED
120Lm/W
220-240V AC 50/60 Hz
Surface
W:33mm H:33mm
3000K-4000K-6500K
>80
DALI / 1-10V
IP40



LED



IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
LND50.S/33.11	Surface	11W	1320Lm	>80	3000-4000-6500K	33x33x500mm
LND50.S/33.16	Surface	16W	1920Lm	>80	3000-4000-6500K	33x33x500mm
LND100.S/33.22	Surface	22W	2640Lm	>80	3000-4000-6500K	33x33x1000mm
LND100.S/33.32	Surface	32W	3840Lm	>80	3000-4000-6500K	33x33x1000mm
LND120.S/33.27	Surface	27W	3240Lm	>80	3000-4000-6500K	33x33x1200mm
LND120.S/33.19	Surface	39W	4680Lm	>80	3000-4000-6500K	33x33x1200mm
LND150.S/33.33	Surface	33W	3960Lm	>80	3000-4000-6500K	33x33x1500mm
LND150.S/33.48	Surface	48W	5760Lm	>80	3000-4000-6500K	33x33x1500mm
LND200.S/33.44	Surface	44W	5280Lm	>80	3000-4000-6500K	33x33x2000mm
LND200.S/33.64	Surface	64W	7680Lm	>80	3000-4000-6500K	33x33x2000mm
LND250.S/33.55	Surface	55W	6600Lm	>80	3000-4000-6500K	33x33x2500mm
LND250.S/33.80	Surface	80W	9600Lm	>80	3000-4000-6500K	33x33x2500mm
LND300.S/33.66	Surface	66W	7920Lm	>80	3000-4000-6500K	33x33x3000mm
LND300.S/33.96	Surface	96W	11520Lm	>80	3000-4000-6500K	33x33x3000mm