




## LARA



**Body**  
**Diffuser**  
**Source of light**  
**Lumen/Watt**  
**Input voltage**  
**Mounting**  
**Power factor**  
**Light color**  
**IP rating**  
**Options**  
**CRI**  
**Led lifetime**

Die cast aluminum  
Opal PMMA  
Power LED  
130Lm/W  
220-240V AC 50/60 Hz  
Recessed ceiling mounting  
95+  
3000-4000-6500K  
IP20-IP44  
EMG-DALI  
80+  
100.000+



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
LRA.2022.40	40W	5000Lm	95+	80+	3000-4000-6500K	1300gr	Ø:2x175mm	H:192 W:384 D:120mm
LRA.2022.32	32W	4000Lm	95+	80+	3000-4000-6500K	1100gr	Ø:2x160mm	H:175 W:350 D:120mm
LRA.2022.24	24W	3500Lm	95+	80+	3000-4000-6500K	910gr	Ø:2x130mm	H:147 W:294 D:120mm
LRA.2022.16	16W	2000Lm	95+	80+	3000-4000-6500K	690gr	Ø:2x105mm	H:117 W:234 D:120mm
LRA.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	505gr	Ø:2x85mm	H:97 W:194 D:120mm







































