

MANTA




Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Aluminum reflector - PMMA
 COB LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



IP20



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
MNT.2022.50	50W	6500Lm	95+	80+	3000-4000-6500K	1300gr	Ø:2x175mm	H:192 W:384 D:120mm
MNT.2022.36	36W	4680Lm	95+	80+	3000-4000-6500K	910gr	Ø:2x160mm	H:175 W:350 D:120mm
MNT.2022.24	24W	3120Lm	95+	80+	3000-4000-6500K	690gr	Ø:2x130mm	H:147 W:294 D:120mm
MNT.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	595gr	Ø:2x105mm	H:117 W:234 D:120mm
MNT.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	505gr	Ø:2x85mm	H:97 W:194 D:120mm