


MATE



Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Opal PMMA
 Power LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
MTE.2022.25	25W	3000Lm	95+	80+	3000-4000-6500K	660gr	Ø:210mm	Ø:240 H:58 mm
MTE.2022.20	20W	2500Lm	95+	80+	3000-4000-6500K	470gr	Ø:180mm	Ø:200 H:58 mm
MTE.2022.16	16W	2000Lm	95+	80+	3000-4000-6500K	360gr	Ø:130mm	Ø:150 H:58 mm
MTE.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	300gr	Ø:105mm	Ø:120 H:55 mm
MTE.2022.8	8W	1000Lm	95+	80+	3000-4000-6500K	280gr	Ø:90mm	Ø:108 H:40 mm
MTE.2022.6	6W	750Lm	95+	80+	3000-4000-6500K	150gr	Ø:70mm	Ø:80 H:40 mm