



MOON UP&DOWN




Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Suspended
Dimensions	W:87mm H:87mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40



LED



IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
MON50/87.22	Suspended Up&Down	22W	2640Lm	>80	3000-4000-6500K	87x87x500mm
MON50/87.32	Suspended Up&Down	32W	3840Lm	>80	3000-4000-6500K	87x87x500mm
MON100/87.44	Suspended Up&Down	44W	5280Lm	>80	3000-4000-6500K	87x87x1000mm
MON100/87.64	Suspended Up&Down	64W	7680Lm	>80	3000-4000-6500K	87x87x1000mm
MON120/87.54	Suspended Up&Down	54W	6480Lm	>80	3000-4000-6500K	87x87x1200mm
MON120/87.78	Suspended Up&Down	78W	9360Lm	>80	3000-4000-6500K	87x87x1200mm
MON150/87.66	Suspended Up&Down	66W	7920Lm	>80	3000-4000-6500K	87x87x1500mm
MON150/87.96	Suspended Up&Down	96W	11520Lm	>80	3000-4000-6500K	87x87x1500mm
MON200/87.88	Suspended Up&Down	88W	10560Lm	>80	3000-4000-6500K	87x87x2000mm
MON200/87.128	Suspended Up&Down	128W	15360Lm	>80	3000-4000-6500K	87x87x2000mm
MON250/87.110	Suspended Up&Down	110W	13200Lm	>80	3000-4000-6500K	87x87x2500mm
MON250/87.160	Suspended Up&Down	160W	19200Lm	>80	3000-4000-6500K	87x87x2500mm
MON300/87.132	Suspended Up&Down	132W	15840Lm	>80	3000-4000-6500K	87x87x3000mm
MON300/87.192	Suspended Up&Down	192W	23040Lm	>80	3000-4000-6500K	87x87x3000mm