




MUNO SUSPENDED



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Suspended
Dimensions	W:70mm H:50mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
MUNO60.SU/56.18	Suspended	18W	1980Lm	>80	3000-4000-6500K	70x50x570mm
MUNO120.SU/112.35	Suspended	35W	3850Lm	>80	3000-4000-6500K	70x50x1120mm
MUNO150.SU/150.50	Suspended	50W	5500Lm	>80	3000-4000-6500K	70x50x1500mm
MUNO200.SU/200.66	Suspended	66W	7250Lm	>80	3000-4000-6500K	70x50x2000mm
MUNO250.SU/250.82	Suspended	82W	9020Lm	>80	3000-4000-6500K	70x50x2500mm
MUNO300.SU/300.99	Suspended	99W	10890Lm	>80	3000-4000-6500K	70x50x3000mm