


OCEAN SUSPENDED



Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating

Extruded Aluminum
 Opal PMMA-Micro Prismatic
 Power LED
 120Lm/W
 220-240V AC 50/60 Hz
 Suspended
 W:50mm H:50mm
 3000K-4000K-6500K
 >80
 DALI / 1-10V
 IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
OCN50/50.11	Suspended	11W	1320Lm	>80	3000-4000-6500K	50x50x500mm
OCN50/50.16	Suspended	16W	1920Lm	>80	3000-4000-6500K	50x50x500mm
OCN100/50.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	50x50x1000mm
OCN100/50.32	Suspended	32W	3840Lm	>80	3000-4000-6500K	50x50x1000mm
OCN120/50.27	Suspended	27W	3240Lm	>80	3000-4000-6500K	50x50x1200mm
OCN120/50.19	Suspended	39W	4680Lm	>80	3000-4000-6500K	50x50x1200mm
OCN150/50.33	Suspended	33W	3960Lm	>80	3000-4000-6500K	50x50x1500mm
OCN150/50.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	50x50x1500mm
OCN200/50.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	50x50x2000mm
OCN200/50.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	50x50x2000mm
OCN250/50.55	Suspended	55W	6600Lm	>80	3000-4000-6500K	50x50x2500mm
OCN250/50.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	50x50x2500mm
OCN300/50.66	Suspended	66W	7920Lm	>80	3000-4000-6500K	50x50x3000mm
OCN300/50.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	50x50x3000mm