

OCEAN SURFACE




Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Surface
Dimensions	W:50mm H:50mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40



LED



IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
OCN50.S/50.11	Surface	11W	1320Lm	>80	3000-4000-6500K	50x50x500mm
OCN50.S/50.16	Surface	16W	1920Lm	>80	3000-4000-6500K	50x50x500mm
OCN100.S/50.22	Surface	22W	2640Lm	>80	3000-4000-6500K	50x50x1000mm
OCN100.S/50.32	Surface	32W	3840Lm	>80	3000-4000-6500K	50x50x1000mm
OCN120.S/50.27	Surface	27W	3240Lm	>80	3000-4000-6500K	50x50x1200mm
OCN120.S/50.19	Surface	39W	4680Lm	>80	3000-4000-6500K	50x50x1200mm
OCN150.S/50.33	Surface	33W	3960Lm	>80	3000-4000-6500K	50x50x1500mm
OCN150.S/50.48	Surface	48W	5760Lm	>80	3000-4000-6500K	50x50x1500mm
OCN200.S/50.44	Surface	44W	5280Lm	>80	3000-4000-6500K	50x50x2000mm
OCN200.S/50.64	Surface	64W	7680Lm	>80	3000-4000-6500K	50x50x2000mm
OCN250.S/50.55	Surface	55W	6600Lm	>80	3000-4000-6500K	50x50x2500mm
OCN250.S/50.80	Surface	80W	9600Lm	>80	3000-4000-6500K	50x50x2500mm
OCN300.S/50.66	Surface	66W	7920Lm	>80	3000-4000-6500K	50x50x3000mm
OCN300.S/50.96	Surface	96W	11520Lm	>80	3000-4000-6500K	50x50x3000mm