

PURE SUSPENDED



Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating

Extruded Aluminum
 Opal PMMA-Micro Prismatic
 Power LED
 120Lm/W
 220-240V AC 50/60 Hz
 Suspended
 Ø:85mm
 3000K-4000K-6500K
 >80
 DALI / 1-10V
 IP40



LED



IP40

Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
PRE50/87.11	Suspended	11W	1320Lm	>80	3000-4000-6500K	Ø:85x500mm
PRE50/87.16	Suspended	16W	1920Lm	>80	3000-4000-6500K	Ø:85x500mm
PRE100/87.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	Ø:85x1000mm
PRE100/87.32	Suspended	32W	3840Lm	>80	3000-4000-6500K	Ø:85x1000mm
PRE120/87.27	Suspended	27W	3240Lm	>80	3000-4000-6500K	Ø:85x1200mm
PRE120/87.39	Suspended	39W	4680Lm	>80	3000-4000-6500K	Ø:85x1200mm
PRE150/87.33	Suspended	33W	3960Lm	>80	3000-4000-6500K	Ø:85x1500mm
PRE150/87.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	Ø:85x1500mm
PRE200/87.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	Ø:85x2000mm
PRE200/87.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	Ø:85x2000mm
PRE250/87.55	Suspended	55W	6600Lm	>80	3000-4000-6500K	Ø:85x2500mm
PRE250/87.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	Ø:85x2500mm
PRE300/87.66	Suspended	66W	7920Lm	>80	3000-4000-6500K	Ø:85x3000mm
PRE300/87.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	Ø:85x3000mm