


RINGO



Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Opal PMMA
 Power LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
RNG.2022.40	40W	5000Lm	95+	80+	3000-4000-6500K	1300gr	Ø:2x175mm	H:192 W:384 D:120mm
RNG.2022.32	32W	4000Lm	95+	80+	3000-4000-6500K	1100gr	Ø:2x160mm	H:175 W:350 D:120mm
RNG.2022.24	24W	3500Lm	95+	80+	3000-4000-6500K	910gr	Ø:2x130mm	H:147 W:294 D:120mm
RNG.2022.16	16W	2000Lm	95+	80+	3000-4000-6500K	690gr	Ø:2x105mm	H:117 W:234 D:120mm
RNG.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	505gr	Ø:2x85mm	H:97 W:194 D:120mm