

## RIVA




**Body**  
**Diffuser**  
**Source of light**  
**Lumen/Watt**  
**Input voltage**  
**Mounting**  
**Power factor**  
**Light color**  
**IP rating**  
**Options**  
**CRI**  
**Led lifetime**

Die cast aluminum  
 Aluminum reflector - PMMA  
 COB LED  
 130Lm/W  
 220-240V AC 50/60 Hz  
 Recessed ceiling mounting  
 95+  
 3000-4000-6500K  
 IP20-IP44  
 EMG-DALI  
 80+  
 100.000+



IP20



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
RVA.2022.50	50W	6500Lm	95+	80+	3000-4000-6500K	1300gr	Ø:2x175mm	H:192 W:384 D:120mm
RVA.2022.36	36W	4680Lm	95+	80+	3000-4000-6500K	910gr	Ø:2x160mm	H:175 W:350 D:120mm
RVA.2022.24	24W	3120Lm	95+	80+	3000-4000-6500K	690gr	Ø:2x130mm	H:147 W:294 D:120mm
RVA.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	595gr	Ø:2x105mm	H:117 W:234 D:120mm
RVA.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	505gr	Ø:2x85mm	H:97 W:194 D:120mm