


## RIVER SUSPENDED



**Body**  
**Diffuser**  
**Source of Light**  
**Lumen/Watt**  
**Input Voltage**  
**Mounting**  
**Dimensions**  
**Light Color**  
**CRI**  
**Dim**  
**IP Rating**

Extruded Aluminum  
 Opal PMMA-Micro Prismatic  
 Power LED  
 120Lm/W  
 220-240V AC 50/60 Hz  
 Suspended  
 W:35mm H:60mm  
 3000K-4000K-6500K  
 >80  
 DALI / 1-10V  
 IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
RVR50/35.11	Suspended	11W	1320Lm	>80	3000-4000-6500K	35x60x500mm
RVR50/35.16	Suspended	16W	1920Lm	>80	3000-4000-6500K	35x60x500mm
RVR100/35.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	35x60x1000mm
RVR100/35.32	Suspended	32W	3840Lm	>80	3000-4000-6500K	35x60x1000mm
RVR120/35.27	Suspended	27W	3240Lm	>80	3000-4000-6500K	35x60x1200mm
RVR120/35.19	Suspended	39W	4680Lm	>80	3000-4000-6500K	35x60x1200mm
RVR150/35.33	Suspended	33W	3960Lm	>80	3000-4000-6500K	35x60x1500mm
RVR150/35.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	35x60x1500mm
RVR200/35.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	35x60x2000mm
RVR200/35.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	35x60x2000mm
RVR250/35.55	Suspended	55W	6600Lm	>80	3000-4000-6500K	35x60x2500mm
RVR250/35.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	35x60x2500mm
RVR300/35.66	Suspended	66W	7920Lm	>80	3000-4000-6500K	35x60x3000mm
RVR300/35.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	35x60x3000mm