




RIVER SURFACE



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Surface
Dimensions	W:35mm H:60mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
RVR50.S/35.11	Surface	11W	1320Lm	>80	3000-4000-6500K	35x60x500mm
RVR50.S/35.16	Surface	16W	1920Lm	>80	3000-4000-6500K	35x60x500mm
RVR100.S/35.22	Surface	22W	2640Lm	>80	3000-4000-6500K	35x60x1000mm
RVR100.S/35.32	Surface	32W	3840Lm	>80	3000-4000-6500K	35x60x1000mm
RVR120.S/35.27	Surface	27W	3240Lm	>80	3000-4000-6500K	35x60x1200mm
RVR120.S/35.19	Surface	39W	4680Lm	>80	3000-4000-6500K	35x60x1200mm
RVR150.S/35.33	Surface	33W	3960Lm	>80	3000-4000-6500K	35x60x1500mm
RVR150.S/35.48	Surface	48W	5760Lm	>80	3000-4000-6500K	35x60x1500mm
RVR200.S/35.44	Surface	44W	5280Lm	>80	3000-4000-6500K	35x60x2000mm
RVR200.S/35.64	Surface	64W	7680Lm	>80	3000-4000-6500K	35x60x2000mm
RVR250.S/35.55	Surface	55W	6600Lm	>80	3000-4000-6500K	35x60x2500mm
RVR250.S/35.80	Surface	80W	9600Lm	>80	3000-4000-6500K	35x60x2500mm
RVR300.S/35.66	Surface	66W	7920Lm	>80	3000-4000-6500K	35x60x3000mm
RVR300.S/35.96	Surface	96W	11520Lm	>80	3000-4000-6500K	35x60x3000mm