




ROCK RECESSED



| | |
|------------------------|---------------------------|
| Body | Extruded Aluminum |
| Diffuser | Opal PMMA-Micro Prismatic |
| Source of Light | Power LED |
| Lumen/Watt | 120Lm/W |
| Input Voltage | 220-240V AC 50/60 Hz |
| Mounting | Recessed |
| Dimensions | W:98mm H:60mm |
| Light Color | 3000K-4000K-6500K |
| CRI | >80 |
| Dim | DALI / 1-10V |
| IP Rating | IP40 |

CE  LED  IP40



| Product Code | Product | Watt | Lumen | CRI | Light Color | Dimensions mm |
|--------------|----------|------|---------|-----|-----------------|---------------|
| RCK50/98.11 | Recessed | 11W | 1320Lm | >80 | 3000-4000-6500K | 98x60x500mm |
| RCK50/98.16 | Recessed | 16W | 1920Lm | >80 | 3000-4000-6500K | 98x60x500mm |
| RCK100/98.22 | Recessed | 22W | 2640Lm | >80 | 3000-4000-6500K | 98x60x1000mm |
| RCK100/98.32 | Recessed | 32W | 3840Lm | >80 | 3000-4000-6500K | 98x60x1000mm |
| RCK120/98.27 | Recessed | 27W | 3240Lm | >80 | 3000-4000-6500K | 98x60x1200mm |
| RCK120/98.39 | Recessed | 39W | 4680Lm | >80 | 3000-4000-6500K | 98x60x1200mm |
| RCK150/98.33 | Recessed | 33W | 3960Lm | >80 | 3000-4000-6500K | 98x60x1500mm |
| RCK150/98.48 | Recessed | 48W | 5760Lm | >80 | 3000-4000-6500K | 98x60x1500mm |
| RCK200/98.44 | Recessed | 44W | 5280Lm | >80 | 3000-4000-6500K | 98x60x2000mm |
| RCK200/98.64 | Recessed | 64W | 7680Lm | >80 | 3000-4000-6500K | 98x60x2000mm |
| RCK250/98.55 | Recessed | 55W | 6600Lm | >80 | 3000-4000-6500K | 98x60x2500mm |
| RCK250/98.80 | Recessed | 80W | 9600Lm | >80 | 3000-4000-6500K | 98x60x2500mm |
| RCK300/98.66 | Recessed | 66W | 7920Lm | >80 | 3000-4000-6500K | 98x60x3000mm |
| RCK300/98.96 | Recessed | 96W | 11520Lm | >80 | 3000-4000-6500K | 98x60x3000mm |