




## SOLAR RECESSED



**Body**  
**Diffuser**  
**Source of Light**  
**Lumen/Watt**  
**Input Voltage**  
**Mounting**  
**Dimensions**  
**Light Color**  
**CRI**  
**Dim**  
**IP Rating**

Extruded Aluminum  
Opal PMMA-Micro Prismatic  
Power LED  
120Lm/W  
220-240V AC 50/60 Hz  
Recessed  
W:68mm H:37mm  
3000K-4000K-6500K  
>80  
DALI / 1-10V  
IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
SLR50/68.11	Recessed	11W	1320Lm	>80	3000-4000-6500K	68x37x500mm
SLR50/68.16	Recessed	16W	1920Lm	>80	3000-4000-6500K	68x37x500mm
SLR100/68.22	Recessed	22W	2640Lm	>80	3000-4000-6500K	68x37x1000mm
SLR100/68.32	Recessed	32W	3840Lm	>80	3000-4000-6500K	68x37x1000mm
SLR120/68.27	Recessed	27W	3240Lm	>80	3000-4000-6500K	68x37x1200mm
SLR120/68.39	Recessed	39W	4680Lm	>80	3000-4000-6500K	68x37x1200mm
SLR150/68.33	Recessed	33W	3960Lm	>80	3000-4000-6500K	68x37x1500mm
SLR150/68.48	Recessed	48W	5760Lm	>80	3000-4000-6500K	68x37x1500mm
SLR200/68.44	Recessed	44W	5280Lm	>80	3000-4000-6500K	68x37x2000mm
SLR200/68.64	Recessed	64W	7680Lm	>80	3000-4000-6500K	68x37x2000mm
SLR250/68.55	Recessed	55W	6600Lm	>80	3000-4000-6500K	68x37x2500mm
SLR250/68.80	Recessed	80W	9600Lm	>80	3000-4000-6500K	68x37x2500mm
SLR300/68.66	Recessed	66W	7920Lm	>80	3000-4000-6500K	68x37x3000mm
SLR300/68.96	Recessed	96W	11520Lm	>80	3000-4000-6500K	68x37x3000mm