


STORM RECESSED



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Recessed
Dimensions	W:90mm H:45mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
STM50/90.11	Recessed	11W	1320Lm	>80	3000-4000-6500K	90x45x500mm
STM50/90.16	Recessed	16W	1920Lm	>80	3000-4000-6500K	90x45x500mm
STM100/90.22	Recessed	22W	2640Lm	>80	3000-4000-6500K	90x45x1000mm
STM100/90.32	Recessed	32W	3840Lm	>80	3000-4000-6500K	90x45x1000mm
STM120/90.27	Recessed	27W	3240Lm	>80	3000-4000-6500K	90x45x1200mm
STM120/90.39	Recessed	39W	4680Lm	>80	3000-4000-6500K	90x45x1200mm
STM150/90.33	Recessed	33W	3960Lm	>80	3000-4000-6500K	90x45x1500mm
STM150/90.48	Recessed	48W	5760Lm	>80	3000-4000-6500K	90x45x1500mm
STM200/90.44	Recessed	44W	5280Lm	>80	3000-4000-6500K	90x45x2000mm
STM200/90.64	Recessed	64W	7680Lm	>80	3000-4000-6500K	90x45x2000mm
STM250/90.55	Recessed	55W	6600Lm	>80	3000-4000-6500K	90x45x2500mm
STM250/90.80	Recessed	80W	9600Lm	>80	3000-4000-6500K	90x45x2500mm
STM300/90.66	Recessed	66W	7920Lm	>80	3000-4000-6500K	90x45x3000mm
STM300/90.96	Recessed	96W	11520Lm	>80	3000-4000-6500K	90x45x3000mm