


ULTRA



Body
Diffuser
Source of light
Lumen/Watt
Input voltage
Mounting
Power factor
Light color
IP rating
Options
CRI
Led lifetime

Die cast aluminum
 Opal PMMA
 Power LED
 130Lm/W
 220-240V AC 50/60 Hz
 Recessed ceiling mounting
 95+
 3000-4000-6500K
 IP20-IP44
 EMG-DALI
 80+
 100.000+



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
ULT.2022.25	25W	3000Lm	95+	80+	3000-4000-6500K	1200gr	Ø:210mm	W:227 H:227 D:85 mm
ULT.2022.20	20W	2500Lm	95+	80+	3000-4000-6500K	860gr	Ø:175mm	W:192 H:192 D:85 mm
ULT.2022.16	16W	2000Lm	95+	80+	3000-4000-6500K	720gr	Ø:160mm	W:175 H:175 D:85 mm
ULT.2022.12	12W	1500Lm	95+	80+	3000-4000-6500K	580gr	Ø:130mm	W:147 H:147 D:80 mm
ULT.2022.8	8W	1000Lm	95+	80+	3000-4000-6500K	420gr	Ø:105mm	W:117 H:117 D:70 mm
ULT.2022.6	6W	750Lm	95+	80+	3000-4000-6500K	370gr	Ø:85mm	W:97 H:97 D:70 mm