

## WAVE




**Body**  
**Diffuser**  
**Source of light**  
**Lumen/Watt**  
**Input voltage**  
**Mounting**  
**Power factor**  
**Light color**  
**IP rating**  
**Options**  
**CRI**  
**Led lifetime**

Die cast aluminum  
 Aluminum reflector - PMMA  
 COB LED  
 130Lm/W  
 220-240V AC 50/60 Hz  
 Recessed ceiling mounting  
 95+  
 3000-4000-6500K  
 IP20-IP44  
 EMG-DALI  
 80+  
 100.000+



IP20



Product Code	Watt	Lumen	Power Factor	CRI	Light Color	Kg	Cut Size mm	Dimensions mm
WVE.2022.25	25W	3250Lm	95+	80+	3000-4000-6500K	1000gr	Ø:210mm	H:227 D: 85mm
WVE.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	770gr	Ø:175mm	H:192 D: 85mm
WVE.2022.18	18W	2340Lm	95+	80+	3000-4000-6500K	670gr	Ø:160mm	H:175 D: 85mm
WVE.2022.12	12W	1560Lm	95+	80+	3000-4000-6500K	520gr	Ø:130mm	H:147 D: 75mm
WVE.2022.9	9W	1170Lm	95+	80+	3000-4000-6500K	400gr	Ø:105mm	H:117 D: 70mm
WVE.2022.6	6W	780Lm	95+	80+	3000-4000-6500K	380gr	Ø:85mm	H:97 D: 70mm