


WILD SUSPENDED



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Suspended
Dimensions	W:67mm H:84mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
WLD50/67.11	Suspended	11W	1320Lm	>80	3000-4000-6500K	67x84x500mm
WLD50/67.16	Suspended	16W	1920LM	>80	3000-4000-6500K	67x84x500mm
WLD100/67.22	Suspended	22W	2640Lm	>80	3000-4000-6500K	67x84x1000mm
WLD100/67.32	Suspended	32W	3840Lm	>80	3000-4000-6500K	67x84x1000mm
WLD120/67.27	Suspended	27W	3240Lm	>80	3000-4000-6500K	67x84x1200mm
WLD120/67.19	Suspended	39W	4680Lm	>80	3000-4000-6500K	67x84x1200mm
WLD150/67.33	Suspended	33W	3960Lm	>80	3000-4000-6500K	67x84x1500mm
WLD150/67.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	67x84x1500mm
WLD200/67.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	67x84x2000mm
WLD200/67.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	67x84x2000mm
WLD250/67.55	Suspended	55W	6600Lm	>80	3000-4000-6500K	67x84x2500mm
WLD250/67.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	67x84x2500mm
WLD300/67.66	Suspended	66W	7920Lm	>80	3000-4000-6500K	67x84x3000mm
WLD300/67.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	67x84x3000mm