




## ZONE RECESSED



**Body**  
**Diffuser**  
**Source of Light**  
**Lumen/Watt**  
**Input Voltage**  
**Mounting**  
**Dimensions**  
**Light Color**  
**CRI**  
**Dim**  
**IP Rating**

Extruded Aluminum  
Opal PMMA-Micro Prismatic  
Power LED  
120Lm/W  
220-240V AC 50/60 Hz  
Recessed  
W:46mm H:33mm  
3000K-4000K-6500K  
>80  
DALI / 1-10V  
IP40

CE  LED  IP40



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
ZNE50/46.11	Recessed	11W	1320Lm	>80	3000-4000-6500K	46x33x500mm
ZNE50/46.16	Recessed	16W	1920Lm	>80	3000-4000-6500K	46x33x500mm
ZNE100/46.22	Recessed	22W	2640Lm	>80	3000-4000-6500K	46x33x1000mm
ZNE100/46.32	Recessed	32W	3840Lm	>80	3000-4000-6500K	46x33x1000mm
ZNE120/46.27	Recessed	27W	3240Lm	>80	3000-4000-6500K	46x33x1200mm
ZNE120/46.39	Recessed	39W	4680Lm	>80	3000-4000-6500K	46x33x1200mm
ZNE150/46.33	Recessed	33W	3960Lm	>80	3000-4000-6500K	46x33x1500mm
ZNE150/46.48	Recessed	48W	5760Lm	>80	3000-4000-6500K	46x33x1500mm
ZNE200/46.44	Recessed	44W	5280Lm	>80	3000-4000-6500K	46x33x2000mm
ZNE200/46.64	Recessed	64W	7680Lm	>80	3000-4000-6500K	46x33x2000mm
ZNE250/46.55	Recessed	55W	6600Lm	>80	3000-4000-6500K	46x33x2500mm
ZNE250/46.80	Recessed	80W	9600Lm	>80	3000-4000-6500K	46x33x2500mm
ZNE300/46.66	Recessed	66W	7920Lm	>80	3000-4000-6500K	46x33x3000mm
ZNE300/46.96	Recessed	96W	11520Lm	>80	3000-4000-6500K	46x33x3000mm