


AURA SURFACE



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Surface
Dimensions	W:52mm H:65mm
Light Color	3000K-4000K-6500K
CRI	>80
Options	DALI / 1-10V
IP Rating	IP40
Led lifetime	100.000+



LED



IP40

Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (L:W:H:)
ARA55/52.44	Surface	44W	5280Lm	>80	3000-4000-6500K	52x65x550x550mm
ARA55/52.64	Surface	64W	7680Lm	>80	3000-4000-6500K	52x65x550x550mm
ARA100/52.88	Surface	88W	10560Lm	>80	3000-4000-6500K	52x65x1000x1000mm
ARA100/52.128	Surface	128W	15360Lm	>80	3000-4000-6500K	52x65x1000x1000mm
ARA120/52.105	Surface	105W	12600Lm	>80	3000-4000-6500K	52x65x1200x1200mm
ARA120/52.154	Surface	154W	18480Lm	>80	3000-4000-6500K	52x65x1200x1200mm
ARA150/52.132	Surface	132W	15840Lm	>80	3000-4000-6500K	52x65x1500x1500mm
ARA150/52.192	Surface	192W	23040Lm	>80	3000-4000-6500K	52x65x1500x1500mm
ARA200/52.176	Surface	176W	21120Lm	>80	3000-4000-6500K	52x65x2000x2000mm
ARA200/52.256	Surface	256W	30720Lm	>80	3000-4000-6500K	52x65x2000x2000mm
ARA250/52.220	Surface	220W	26400Lm	>80	3000-4000-6500K	52x65x2500x2500mm
ARA250/52.320	Surface	320W	38400Lm	>80	3000-4000-6500K	52x65x2500x2500mm
ARA300/52.264	Surface	264W	31680Lm	>80	3000-4000-6500K	52x65x3000x3000mm
ARA300/52.384	Surface	384W	46080Lm	>80	3000-4000-6500K	52x65x3000x3000mm