

## AXEL SUSPENDED



<b>Body</b>	Extruded Aluminum
<b>Diffuser</b>	Opal PMMA-Micro Prismatic
<b>Source of Light</b>	Power LED
<b>Lumen/Watt</b>	120Lm/W
<b>Input Voltage</b>	220-240V AC 50/60 Hz
<b>Mounting</b>	Suspended
<b>Dimensions</b>	W:33mm H:33mm
<b>Light Color</b>	3000K-4000K-6500K
<b>CRI</b>	>80
<b>Options</b>	DALI / 1-10V
<b>IP Rating</b>	IP40
<b>Led lifetime</b>	100.000+



LED



IP40

Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (Ø:W:H:)
AXL55.SU/33.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	33x33x550x550mm
AXL55.SU/33.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	33x33x550x550mm
AXL100.SU/33.88	Suspended	88W	10560Lm	>80	3000-4000-6500K	33x33x1000x1000mm
AXL100.SU/33.128	Suspended	128W	15360Lm	>80	3000-4000-6500K	33x33x1000x1000mm
AXL120.SU/33.105	Suspended	105W	12600Lm	>80	3000-4000-6500K	33x33x1200x1200mm
AXL120.SU/33.154	Suspended	154W	18480Lm	>80	3000-4000-6500K	33x33x1200x1200mm
AXL150.SU/33.132	Suspended	132W	15840Lm	>80	3000-4000-6500K	33x33x1500x1500mm
AXL150.SU/33.192	Suspended	192W	23040Lm	>80	3000-4000-6500K	33x33x1500x1500mm
AXL200.SU/33.176	Suspended	176W	21120Lm	>80	3000-4000-6500K	33x33x2000x2000mm
AXL200.SU/33.256	Suspended	256W	30720Lm	>80	3000-4000-6500K	33x33x2000x2000mm
AXL250.SU/33.220	Suspended	220W	26400Lm	>80	3000-4000-6500K	33x33x2500x2500mm
AXL250.SU/33.320	Suspended	320W	38400Lm	>80	3000-4000-6500K	33x33x2500x2500mm
AXL300.SU/33.264	Suspended	264W	31680Lm	>80	3000-4000-6500K	33x33x3000x3000mm
AXL300.SU/33.384	Suspended	384W	46080Lm	>80	3000-4000-6500K	33x33x3000x3000mm