

BRIGHT UP & DOWN SUSPENDED



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Suspended
Dimensions	W:96mm H:106mm
Light Color	3000K-4000K-6500K
CRI	>80
Options	DALI / 1-10V
IP Rating	IP40
Led lifetime	100.000+



LED



IP40

Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (L:W:H:)
BRG60/96.104	Suspended Up&Down	104W	12480Lm	>80	3000-4000-6500K	96x106x600x600mm
BRG60/96.153	Suspended Up&Down	153W	18360Lm	>80	3000-4000-6500K	96x106x600x600mm
BRG90/96.158	Suspended Up&Down	158W	18960Lm	>80	3000-4000-6500K	96x106x900x900mm
BRG90/96.230	Suspended Up&Down	230W	27600Lm	>80	3000-4000-6500K	96x106x900x900mm
BRG100/96.176	Suspended Up&Down	176W	21120Lm	>80	3000-4000-6500K	96x106x1000x1000mm
BRG100/96.256	Suspended Up&Down	256W	30720Lm	>80	3000-4000-6500K	96x106x1000x1000mm
BRG120/96.211	Suspended Up&Down	211W	25320Lm	>80	3000-4000-6500K	96x106x1200x1200mm
BRG120/96.256	Suspended Up&Down	256W	30720Lm	>80	3000-4000-6500K	96x96x1200x1200mm
BRG150/96.264	Suspended Up&Down	264W	31680Lm	>80	3000-4000-6500K	96x106x1500x1500mm
BRG150/96.384	Suspended Up&Down	384W	46080Lm	>80	3000-4000-6500K	96x106x1500x1500mm
BRG200/96.352	Suspended Up&Down	352W	42240Lm	>80	3000-4000-6500K	96x106x2000x2000mm
BRG200/96.512	Suspended Up&Down	512W	61440Lm	>80	3000-4000-6500K	96x106x2000x2000mm
BRG250/96.440	Suspended Up&Down	440W	52800Lm	>80	3000-4000-6500K	96x106x2500x2500mm
BRG250/96.640	Suspended Up&Down	640W	76800Lm	>80	3000-4000-6500K	96X106x2500x2500mm
BRG300/96.528	Suspended Up&Down	528W	63360Lm	>80	3000-4000-6500K	96x106x3000x3000mm
BRG300/96.768	Suspended Up&Down	768W	92160Lm	>80	3000-4000-6500K	96x106x3000x3000mm