


## FORM RECESSED HYGIENIC



<b>Body</b>	DKP Sheet
<b>Diffuser</b>	Opal PMMA-Tempered Glass
<b>Source of Light</b>	Power LED
<b>Lumen/Watt</b>	120Lm/W
<b>Input Voltage</b>	220-240V AC 50/60 Hz
<b>Mounting</b>	Recessed
<b>Dimensions</b>	595x595x H:70mm
<b>Light Color</b>	3000K-4000K-6500K
<b>CRI</b>	>80
<b>Options</b>	DALI / 1-10V
<b>IP Rating</b>	IP65
<b>Led lifetime</b>	100.000+



LED  IP65



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (L:W:H:)
FRM3030/S.70.12	Recessed	12W	1440Lm	>80	3000-4000-6500K	295X295x85mm
FRM3060/S.70.22	Recessed	22W	2640Lm	>80	3000-4000-6500K	295X595x85mm
FRM6060/S.70.36	Recessed	36W	4320Lm	>80	3000-4000-6500K	595X595x85mm
FRM30120/S.70.36	Recessed	36W	4320Lm	>80	3000-4000-6500K	295X1195x85mm
FRM60120/S.70.70	Recessed	70W	8400Lm	>80	3000-4000-6500K	595X1195x85mm
FRM120120/S.70.140	Recessed	140W	16800Lm	>80	3000-4000-6500K	1195X1195x85mm