

PURE SUSPENDED



Body	Extruded Aluminum
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Suspended
Dimensions	W:67mm H:84mm
Light Color	3000K-4000K-6500K
CRI	>80
Options	DALI / 1-10V
IP Rating	IP40
Led lifetime	100.000+



LED



IP40

Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm (L:W:H:)
PRE55.SU/67.44	Suspended	44W	5280Lm	>80	3000-4000-6500K	67x84x550x550mm
PRE55.SU/67.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	67x84x550x550mm
PRE100.SU/67.88	Suspended	88W	10560Lm	>80	3000-4000-6500K	67x84x1000x1000mm
PRE100.SU/67.128	Suspended	128W	15360Lm	>80	3000-4000-6500K	67x84x1000x1000mm
PRE120.SU/67.105	Suspended	105W	12600Lm	>80	3000-4000-6500K	67x84x1200x1200mm
PRE120.SU/67.154	Suspended	154W	18480Lm	>80	3000-4000-6500K	67x84x1200x1200mm
PRE150.SU/67.132	Suspended	132W	15840Lm	>80	3000-4000-6500K	67x84x1500x1500mm
PRE150.SU/67.192	Suspended	192W	23040Lm	>80	3000-4000-6500K	67x84x1500x1500mm
PRE200.SU/67.176	Suspended	176W	21120Lm	>80	3000-4000-6500K	67x84x2000x2000mm
PRE200.SU/67.256	Suspended	256W	30720Lm	>80	3000-4000-6500K	67x84x2000x2000mm
PRE250.SU/67.220	Suspended	220W	26400Lm	>80	3000-4000-6500K	67x84x2500x2500mm
PRE250.SU/67.320	Suspended	320W	38400Lm	>80	3000-4000-6500K	67x84x2500x2500mm
PRE300.SU/67.264	Suspended	264W	31680Lm	>80	3000-4000-6500K	67x84x3000x3000mm
PRE300.SU/67.384	Suspended	384W	46080Lm	>80	3000-4000-6500K	67x84x3000x3000mm