

TITAN SUSPENDED



Body
Diffuser
Source of Light
Lumen/Watt
Input Voltage
Mounting
Dimensions
Light Color
CRI
Dim
IP Rating


Stainless Steel
 Opal PMMA-Micro Prismatic
 Power LED
 120Lm/W
 220-240V AC 50/60 Hz
 Suspended
 W:100 H:80mm
 3000K-4000K-6500K
 >80
 DALI / 1-10V
 IP20



LED



IP20



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
TAN150/100.48	Suspended	48W	5760Lm	>80	3000-4000-6500K	100x80x1500mm
TAN200/100.64	Suspended	64W	7680Lm	>80	3000-4000-6500K	100x80x2000mm
TAN250/100.80	Suspended	80W	9600Lm	>80	3000-4000-6500K	100x80x2500mm
TAN300/100.96	Suspended	96W	11520Lm	>80	3000-4000-6500K	100x80x3000mm
TAN350/100.112	Suspended	112W	13440Lm	>80	3000-4000-6500K	100x80x3500mm
TAN400/100.128	Suspended	128W	15360Lm	>80	3000-4000-6500K	100x80x4000mm
TAN450/100.144	Suspended	144W	17280Lm	>80	3000-4000-6500K	100x80x4500mm
TAN500/100.160	Suspended	160W	19200Lm	>80	3000-4000-6500K	100x80x5000mm