

ATLAS LIGHTING

TITAN SURFACE




Body	Stainless Steel
Diffuser	Opal PMMA-Micro Prismatic
Source of Light	Power LED
Lumen/Watt	120Lm/W
Input Voltage	220-240V AC 50/60 Hz
Mounting	Surface
Dimensions	W:100 H:80mm
Light Color	3000K-4000K-6500K
CRI	>80
Dim	DALI / 1-10V
IP Rating	IP20



LED



IP20



Product Code	Product	Watt	Lumen	CRI	Light Color	Dimensions mm
TAN150.SU/100.48	Surface	48W	5760Lm	>80	3000-4000-6500K	100x80x1500mm
TAN200.SU/100.64	Surface	64W	7680Lm	>80	3000-4000-6500K	100x80x2000mm
TAN250.SU/100.80	Surface	80W	9600Lm	>80	3000-4000-6500K	100x80x2500mm
TAN300.SU/100.96	Surface	96W	11520Lm	>80	3000-4000-6500K	100x80x3000mm
TAN350.SU/100.112	Surface	112W	13440Lm	>80	3000-4000-6500K	100x80x3500mm
TAN400.SU/100.128	Surface	128W	15360Lm	>80	3000-4000-6500K	100x80x4000mm
TAN450.SU/100.144	Surface	144W	17280Lm	>80	3000-4000-6500K	100x80x4500mm
TAN500.SU/100.160	Surface	160W	19200Lm	>80	3000-4000-6500K	100x80x5000mm